
# 尺寸: 55\*85mm 128g铜版纸正反面印刷





使用者指南

中文

### 前言

### 重要提示

- ・请注意所有警告提示并遵守使用者指南内的所有指令。

警告:请勿将本产品放置在有腐蚀性化学物品的地方,以免产品受到腐蚀,被腐蚀可能引起产品故障。

- 请用软布、干布清洁本产品。
- 请勿将本产品放置在温度过高的地方,高温可能导致产品内电
- ●需要维修时清联系授权的维修人员。本产品内有精密电子线路。 未经许可擅自拆卸导致故障,不在本司保修范围内,但用户可以
- •建议使用唯迹原厂线缆。由于使用非唯迹原厂附件导致本
- 产品的任何损坏,不在本司保修范围内,但用户可以付费维修。 ◆本产品已经过RoHS和CE认证,请参考相关国家标准使用和操
- 此使用者指南依据本公司严格测试制定。设计和规格如有变更, 恕不另行通知。

- 3.不要靠近和放置于火中。
- 4.电池使用报废后请按当地的规定处理。
- 5.长期不使用,请充电至60%再放置。
- 6.为了延长电池的使用寿命,建议每三个月进行一次充电保养。

感谢您购买唯迹产品。

- 请认真阅读本使用者指南。
- •请妥善保管使用者指南。将产品交给他人使用时,请务必附带

- 本产品属于精密仪器,请避免使用时掉落、碰撞或承受重击。
- 作。因使用操作不当而造成机器损坏,不在保修范围内,但用户


## 注意事项


- 1.充电不要放置超过24小时。
- 2.应放置于凉爽、干燥及通风的地方存储。


- 7.电池有一定的寿命限制,使用一定时间后,性能会减弱,属正常现象。

# 二、标配清单

包装内包含以下物品







# 四、操作说明

1. 打开/关闭电源

- 长按电源键可以打开或关闭电源。 | 模式切换键(3种模式)短按切换补光 灯模式,本产品有3种模式(CCT模
- 式、RGB模式、特效模式)模式详 情请看界面介绍。 2 色温调节: 向上或向下波轮调节
- 色温,调节范围2500K-9000K。 3 亮度调节:拨动亮度调节拨扭调节 亮度, 亮度调节范围0~100%。

### 2. 显示屏界面说明



- \* 在CCT模式中,可通过色温调节拨轮进行色温调节。
- \* 色温范围为( 2500K-9000K)。
- \* 亮度调节:拨动亮度调节拨扭调节亮度,亮度调节范围0~100%。



- \* 在RGB模式中, 可通过色温调节拨轮进行色相值调节, \* 色相值调节范围0~360°。
- \* 亮度调节: 拨动亮度调节拨扭调节亮度, 亮度调节范围0~100%。





- \* 在特效模式中,通过色温调节波轮可切换20种场景模式。
- \* 亮度调节: 拨动亮度调节拨扭调节亮度, 亮度调节范围0~100%。

### 3. 情景特效模式



9 坏灯泡 Fault Bulb 19 HSI演示(慢) HSI Slow

10 白色呼吸灯 Pulsing 20 HSI演示(快) HSI Fast

## 4. 安装与使用

- 4.1充电方式
- \* Type-C充电, 支持PD快充。
- \* 开机状态充电缓慢,建议关机后再充电。



底部有固定的1/4螺丝孔,可安装在三脚架和其他设备。 4 0 1 五、规格参数

4.2 1/4螺丝接口

ı	型号		号	VL196	色温 2:		2500-9000k±200K	
ı			白色	54pcs	持续工作时间。		最大亮度 > 2h	
ı		灯珠	黄色				最小亮度 > 15h	
ı			RGB	88pcs			取りが没って	
ı		显技	旨	CR <b>I</b> 95+	持续二 , , 光 り 19	功率	12W	
ı		工作	电压	7.4V	R4		76*148*16mm	
ı		电池	容量	3000mAh	持续二 , 分 光 り 19	16.0	70 140 1011111	
ı		充	电	Type-C	光	照角度	120°	
ı		服	ri <del>c</del>	距离	0.3M		0.5M	1M
ı		, m	ise.	亮度	1920Lm		550 <b>l</b> ux	180 <b>l</b> ux
ı		充电时间		PD快充约2小	时 普通3		記电约3小时 (5V/2A)	

\*亭度数据为平均数据,不同灯的亭度会有微小差异。

# 六、维护与保养

Foreward

Instructions

physical shocking it.

can cause the product to malfunction.

repairs on a chargeable basis.

Thank you for purchasing the vijim

•Please read this product manual carefully.

when passing the products on to third parties.

1.对本产品充电完毕时,应拔出USB充电线

2.如长时间不使用本产品,可能会出现不能开机的现象,这可能 由于电池耗尽造成的,只需对本产品充电即可恢复使用,建议每 二个日讲行—次充由

3.由于本产品内置可充电锂电池,而可充电锂电池具有一定的寿 命限制, 在本产品使用数年后性能下降时,请你与售后人员联系 更换内置电池事宜。

5.此设备不防水。

4.在使用时请勿大力磕碰、撞击,以免碰损产品表面,影响使用。

Keep this product manual. Always include this product manual.

•Heed all warnings and follow all instructions in this product

there are corrosive chemicals to protect the product

from corrosion, corrosion may cause the product to malfunction.

•Use only a microfber and dry cloth for cleaning the product.

Operate carefully to not cause any damage by dropping or

•Do not leave the product in excessive heat, high temperatures

Please have the product checked by the authorized service or

agent if your product has some problems. Please note that this

warranty does not apply to repair arising out of the malfunction

of unauthorized disassembly, although you may request such

WARNING: Do not place the product in a place where

д,	Specific	cations			
Model		VL196	Color temperature	2500-9000k±200K	
	White	54pcs	6	Maximum brightness > 2h Minimum	
Lamp beads	Yellow	54pcs	Continuous working time		
Caas	RGB	88pcs Working time			ess> 15h
N	lanifest	CRI95+	Power		
Operating Voltage Battery capacity Charge Illuminance Charge Time		7.4V	size	12W 76*148*16mm	
		3000mAh	size		
		Type-C	Light angle		
		Distance	0.3M	0.5M 120°	
		Maximum Brightness	1920LM	550lux	1M
		2 hours fast charging of PD			
		3 hours Common Charge (5V/2A)			

- . Please plug out the USB charging cable when charging finishes.
- turn on instantly, which is due to dead battery. Please charge the product This product has built-in rechargeable li-ion battery which has limited
- Please do not drop or impact the product to avoid scratches on the surface
- longevity, and when the performance degrades in years use, please contact us to get the battery replaced.
- and it can resume to work. Please charge the product every 3 months regularly



五、	Specific	cations				
Model		VL196	Color temperature	2500-9000k±200K		
White		54pcs		Maximum		
Lamp beads	Yellow	54pcs	Continuous working time		brightness> 2h Minimum	
beads	RGB	88pcs Working time		brightness> 15h		
Manifest Operating Voltage Battery capacity Charge		CRI95+	Power			
		7.4V	size	12W		
		3000mAh	76*148*16m		8*16mm	
		Type-C	Light angle			
		Distance	0.3M	0.5M 120°		
Illi	ıminance	Maximum Brightness	1920LM	550lux 1M		
Charge Time		2 hours fas	2 hours fast charging of PD			
		2 h C Ch (E) (OA)				

\*This is an averaged result, the number might be slightly different on each light.


### 六、Maintenance

2. If you do not use this product for a long time, it might not be able to

. This Product is not water-proof.

Numbers	Scenario	Numbers	Scenario
1	Cop Car	11	Strobe
2	Ambulance	12	RGB Strobe
3	Fire engine	13	Paparazzi
4	Lightning	14	Emergency
5	Fireworks	15	H/L Beam
6	TV	16	Red Flash
7	Cand <b>l</b> e	17	Green Flash
8	Party	18	Blue Flash
9	Fault Bulb	19	HSI Slow
10	Pulsing	20	HSI Fast


- 4.1 Charge Method
- \* Type-c, supports fast charging of PD.



## 3. Scene effect mode


Numbers	Scenario	Numbers	Scenario
1	Cop Car	11	Strobe
2	2 Ambu <b>l</b> ance		RGB Strobe
3	Fire engine	13	Paparazzi
4	Lightning	14	Emergency
5	Fireworks	15	H/L Beam
6	6 TV		Red Flash
7	Cand <b>l</b> e	17	Green Flash
8	Party	18	Blue Flash
9	Fault Bulb	19	HSI Slow

- \* Charge slow when the light is on, Recommend charging after



## 4. Installation and Operation


shut down.



# RGB Mode

④ 亮度调节旋钮

三、产品介绍



⑤1/4拓展螺孔 ⑥ 显示屏

\* In RGB mode, roll up and down wheel adjusts the RGB HSL. \* RGB HSL Range: 0~360°. \* HSL: Roll up and down wheel adjusts HSL brightness, brightness

range is 0~100%.




- \* In effects mode, through the color temperature adjustment wheel can switch 20 scene different modes.
- \* BRIGHTNESS: Roll up and down wheel adjusts Brightness, Brightness range is 0~100%.

# 四、Operation instructions



- product has 3 modes(CCT, RGB, Effects), mode detail will show in below. 1.2 Colour temperature: Roll up and down wheel adjusts the color temperature.
- .3 Brightness : Roll up and down wheel adjusts Brightness, Brightness range is 0~100%.

# 2. Screen Instruction CCT Mode




- \* Color temperature range ( 2500K-9000K). \* BRIGHTNESS: Roll up and down wheel adjusts Brightness,

- temperature range 2500K-9000K.

- \* In CCT mode, the color temperature adjusted by rolling wheel
- Brightness range is 0~100%.

# **≡**、Nomenclature



① Type-C charging port ②Switch ③ Color temperature switch ④ Brightness adjustment knob © 1/4 expansion screw hole © LED Indicator

# Attention

1. Do not leave charging for more than 24 hours.

carry out charging maintenance every three months.


performance will weaken, which is a normal phenomenon.

- Store in a cool, dry and ventilated place. 3. Do not approach or place in the fire.
- 4. Please follow local regulations in order to dispose of scrapped batterio 5. Please charge it to 60% before placing it for a long time. 6. In order to extend the service life of the battery, it is recommended to 7. The battery has a certain life limit. After a certain period of use, the

# 二、Item Check List

Package includes the following items:

Type-C charging cable \* 1



Ballhead \* 1

•Use of original ViJim cable accessories is recommended. Please note that this warranty does not apply to repairs arising out of the malfunction of non-original ViJim accessories, although you may request such repairs on a chargeable basis. •The product is certificated by RoHS and CE. Please operate the product in full compliance with the operation standards. Please

note that this warranty does not apply to repair arising from malfunction, although you may request such repairs on a chargeable basis. •The instructions and information in this manual are based on

thorough,controlled company testing procedures. Further notice will not be given if the design and specifications change.



# MILI®

